



>>>REAL TIME ANALOG HD, 4ch, DIGITAL VIDEO RECORDER



AHD 4ch DVR **HVR4580**

- > Analog High Definition (AHD), HD over Coax Technology, uses Existing Coax Cables & BNC Connectors: no Rewiring necessary!
- > 4ch Digital Video Recorder with H.264 Compression for Best-in-Class Recording and Storage Performance
- > Real Time 1080p Recording at 30fps
- > Supports both AHD and Analog 960H Cameras Simultaneously
- > Self Diagnostics with Hard Disk Drive S.M.A.R.T. Protocol
- > Concurrent Full HD Display on HDMI and VGA Monitor Outputs
- > Powerful Pentaplex Functionality with Simultaneous Live, Recording, Playback, Backup and Network
- > Supports 1 Hard Disk Drive and Data Backup via USB 2.0
- > Network Accessible via Web Browser and included Remote Management Software, ATVision IP
- > Audio: 4 Inputs, 1 Output; Alarm: 4 Inputs, 1 Output
- > IR Remote Control and USB Mouse Included
- > PTZ Camera Control via RS-485
- > Supports Mobile Phone Applications with Apple and Android Operating Systems

AHD 4ch DVR


HVR4580

AHD PRODUCT SERIES


SPECIFICATIONS

MODELS		HVR4580-1TB
V I D E O	Video	4 BNC
	Recording Video Resolution	Up to 1920 x 1080
	Recording Mode	Continuous, Schedule, Event, Network
	Recording Frame/Sec (FPS)	Max. 120fps @ 1920 x 1080
	Search Mode	Calendar, Date / Time, Event, Protect, Capture
	Video Monitor Output	HDMI, VGA
	Monitor Resolution	1080p maximum
N E T W O R K	Monitor Screen Modes	Full, Quad, PIP, Zoom
	Remote Mobile Support	Tive HD (Android, Apple)
	Remote Access	ATVision IP Remote Management Software, Web Browser, Smart Manager
	Web Browsers	IE, Firefox
	No. of simultaneous users	10
G E N E R A L	Remote Monitoring/Control	E-Map support
	Internal HDD	Up to 1 SATA HDD: 4TB Total Capacity
	Audio (In/Out)	4 / 1 (RCA)
	Alarm	Terminal Block 4 Inputs, 1 Output
	Ethernet	10/100 Base Ethernet
	Ethernet Ports	RJ45 Network Port
	HDMI Monitor Output	(Type A)
	VGA Monitor Output	(15-Pin D-Sub)
	USB	2 x USB2.0
	Power Source	12VDC, 2A (Power Adapter & Cable included)
	Operating Temperature	0°C ~ +45°C (+32°F ~ +114°F)
	Humidity	0%RH ~ 90%RH
	Dimension (W x D x H)	11.8 x 8.2 x 1.85in (300 x 209 x 47mm)
Weight	2.2lbs (1.0kg) (without HDD)	
Conformity Certifications	FCC, CE (UL for Power Adapter Only)	

DIMENSIONS



FRONT VIEW



TOP VIEW

ACCESSORIES

LB3S Recorder Lockbox



ATVision IP Remote Management Software

Minimum System Requirements for ATVision IP Software

- Operating System: Microsoft Windows 7 (or 8) Professional/Enterprise/Ultimate
- CPU: Intel Core i7; RAM: 4GB; Ethernet connection: 1Gbps
- Graphics card: Gaming rated, with 1GB at 1080p for single monitor; 2GB at 1080p for multiple monitors
- HDD's: 7200RPM and 64MB cache; 1 separate HDD for operating system and software; and 1 (2TB) HDD for recording (refer to IP storage calculator)