



ADVANCED
TECHNOLOGY
VIDEO

PERFORMANCE SERIES

>>>700TVL, TRUE DAY/NIGHT,
WEATHERPROOF, IR BULLET CAMERA

IR BULLET CAMERA

BHR7212SR



- > Super High Resolution 700TVL w/Excellent Color Reproduction
- > High Performance 1/3" Sony Super-HAD II CCD Technology
- > True Day / Night Functionality for Low-Light Applications
- > 2.8~12mm Varifocal DC Auto-Iris
- > Smart IR LEDs with 80ft Coverage
- > Through Mount Wiring (TMW) Feature for Easy and Clean Installation
- > 2D Digital Noise Reduction (DNR) for Excellent Picture Quality and Smaller File Sizes
- > IP67 Weatherproof Rating
- > 12VDC - Power Adapter Included

IR BULLET CAMERA

BHR7212SR

PERFORMANCE SERIES

SPECIFICATIONS

MODEL	BHR7212SR	
POWER	Power Source	12VDC (+/- 10%)
	Power Consumption	4.5 Watts (IR LEDs On)
GENERAL	Image Sensor	1/3" Sony EXview HAD CCD II
	Total Number of Pixels	1020(H) x 508(V)
	Scanning System	2:1 Interlace
	Scanning Frequency	15.734KHz(H) x 59.94Hz(V)
	Sync. System	Internal
	Electronic Shutter	1/60 ~ 1/10,000 sec
VIDEO	Resolution	700TVL
	Min. Illumination	0.1 lux (Color) @ F1.2, 50 IRE, 0 Lux (B/W w/IR LED on)
	S/N Ratio	>50dB (AGC OFF)
	Video Output	1.0Vp-p @ 75ohm, Composite
	Smart IR LED's	IR LED 30EA
	IR LED Lighting Distance	80ft (25M) Range
FUNCTION	TRUE Day/Night	Auto
	2D-DNR	On
	Auto Exposure	On
	Smart IR	ON
	Gamma	0.45
	Automatic Gain Control	Auto
	Auto White Balance	Auto (ATW)
CONNECTOR	Power Input	2-Pin Screw Terminal Block
	Video Output	BNC
	Lens mount	Fixed
	Lens	2.8~12mm Varifocal DC Auto-Iris ICR
	Operating Temperature	14°F~122°F (-10°C~+50°C)
	Operating Humidity	0~96% (non-condensing)
	Environmental Rating	IP67
	External Dimension	ø2.6" x 3.8" x 6.7" (ø66 x 97 x 171 mm)
Weight	1.06lb (.48kg)	
Conformity Certifications	FCC, CE, RoHS	

DIMENSIONS

