COVERT COLOR CAMERAS

HEIGHT-STRIP (HS) DAY / NIGHT COVERT COLOR CAMERA

FS100H

- ► High Resolution (550TVL) Day / Night Color Camera in a Covert Height-Strip Housing
- ▶ Graduated and Color Coded in 1-Foot and 6" Increments for Easy Height Identification
- 3.7mm Fixed Iris Wide-Angle Lens for Wide Area Coverage
- Swivel Bracket Allows Adjustment of the Cameras Wide-Angle Lens to Accommodate Double Doors
- Black Anodized Aluminum Housing to Match Standard Commercial Doorframe
- Standard BNC Connector
- Camera Height is Adjustable from the 5½' Level (default) to the 5' Level
- Wall-Mount Swivel Bracket included
- ▶ 12VDC Power Supply included

MINI-STRIP (MS) DAY / NIGHT COVERT COLOR CAMERA

FS150H

- High Resolution (550TVL) Day / Night Color Camera in a Covert Mini-Strip Housing
- Black Faceplate
- 3.7mm Fixed Iris Wide-Angle Lens for Wide Area Coverage
- Unique Design Permits Horizontal (Above Door) and Vertical (Beside Door) Installations
- Swivel Bracket Allows Adjustment of the Cameras Wide-Angle Lens to Cover Multiple Wide-Angle Applications
- Black Anodized Aluminum Housing to Match Standard Commercial Doorframe
- Standard BNC Connector
- ▶ 12VDC Power Supply Included






FS100H / FS150H

SPECIALTY
CAMERA SERIES

SPECIFICATIONS

MODEL		FS100H ~ Color, Covert Camera, Height-Strip Housing
MODEL		FS150H ~ Color, Covert Camera, Mini-Strip Housing
V I D E O	Image Sensor	1/3" CCD, 768 (H) x 494 (V) Pixels
	Resolution	550TVL (Color); 600TVL (B/W)
	Pinhole Lens	3.7mm fixed iris
	Electronic Iris	1/50 (1/60) ~ 1/100,000 Sec.
	Minimum Illum.	0.8 lux, (F1.2) Color: 0.02 (F1.2) B/W
	Video Output	1.0Vp-p (75-ohms), Video BNC
	Video Mode	NTSC-CCIR
G E N E R A	Camera Connectors	BNC / Power
	Dimensions (WxHxD):	(HS) 1.75" x 34.5" x 1.375" (44.45mm x 876mm x 34.9mm)
		(MS) 1.75" x 6.3" x 1.375" (44.45mm x 160mm x 34.9mm)
	Weight	(HS) 2.4 lbs (1.1 kg)
		(MS) 1.0 lbs (0.45 kg)
	Power	12 VDC, 120 ma
L	Operating Temperature	14°F ~ 122°F (-10°C ~ + 50°C)

DIMENSIONS





1" (25.4mm)

