



>>>2MP HD ANALOG COVERT CAMERA

HEIGHT-STRIP COVERT CAMERA

HDHS243

- > High Definition Analog (HD Analog) utilizes existing Coax Cables & BNC Connectors, allowing mega-pixel video images without any rewiring necessary
- > Covert HD Analog Camera in Height Strip Housing with 2MP, 1920 x 1080 Full HD Resolution
- > AHD or CVBS protocol selectable --- engineered to work with ATV's HD Analog and Legacy Digital Video Recorders (DVR) for Maximum Stability and Performance
- > Graduated and Color Coded Height Measurements in both U.S. and Metric Dimensions
- > Included Swivel Bracket for Horizontal and Exclusive 5° Tilt Lever for Vertical Camera Adjustments eliminates need for Separate Bracket
- > 4.3mm Wide Angle Pinhole Lens for Double Door Coverage
- > Progressive Scanning for the Sharpest Video Motion Images
- > Long Distance, Real-Time, Transmission of Video over 1600ft on RG6U Coax Cable
- > True Day / Night and Digital Wide Dynamic Range (DWDR) Functionality for all Lighting Conditions
- > Back Light Compensation (BLC), Defog and Sens-Up Functionality
- > OSD Control via Coax Cable using UTC
- > Supported by ATVision IP Remote Management Client Software for Windows and Mac PC's and Mobile Applications for Apple and Android Operating Systems
- > Digital Noise Reduction 3DNR, Video Motion Detection and Privacy Masking
- > 12VDC Power Source



HEIGHT STRIP COVERT CAMERA


HDHS243

HD ANALOG PRODUCT SERIES

SPECIFICATIONS

MODEL		HDHS243
C A M E R A	Image Sensor	1/2.9" Sony CMOS
	Min. Illumination	Color: 1.0Lux (Color); 0.1Lux (B/W) F2.0
	Scanning Mode	Progressive Scan
	Wide Dynamic Range	Digital
	Video Frame Rate	1920 x 1080p (AHD) or 700TVL (CVBS) @ 30fps
	Video Output	AHD / CVBS Selectable
	Signal Noise Ratio	More than 50dB (AGC off)
	Camera Control	OSD (Coaxial Communication)
	F U N C T I O N S	Shutter
AGC		1~15
Sens-Up		Off / Auto
Brightness		1~100
DWDR		Off / On / Auto
Defog		Off / Auto
Day & Night		Auto / Color / B&W
Backlight		Off / BLC / HSBLC
Camera Title		Off / On
D-Effect		Off / Freeze / Mirror / Neg.Image
Digital Noise Reduction		2DNR, 3DNR
Motion Detection		4 zones
Privacy Masking		4 zones
G E N E R A L	Video Mode	NTSC / PAL
	Composite Video Out	BNC (AHD / CVBS)
	Transmission Distance	Coax Cable, RG6U (5C-2V), 1650ft (500m); RG59 (3C-2V), 990ft (300m)
	Lens	4.3mm Fixed Pinhole, Wide Angle Lens
	Operating Humidity	0 ~ 90% (non-condensing)
	Operating Temperature	14° F - 122° F (-10°C - +50°C)
	Power Source	Barrel Jack, DC12V
	Power Consumption	DC12V - 180mA, 2.2W
	Dimensions (D x H x W)	2.1 x 34.3 x 1.6in (55 x 872 x 43mm)
	Weight	3.3lbs (1.44kg)
Conformity Certifications	FCC, CE	

DIMENSIONS



ATVision IP Remote Management Software

Range of View with H.S. Camera

