



ADVANCED
TECHNOLOGY
VIDEO

IP PRODUCT SERIES

>>> 2MP, TRIPLE STREAM, WDR,
30X, IR SPEED DOME

IP 30X PTZ SPEED DOME

IPSD302TWI





ONVIF | S

- > Brilliant Video Quality with 2MP Full HD, 1920 x 1080 Resolution
- > 1/2.8" Sony Exmor CMOS
- > True Day/Night and WDR Functionality for all Lighting Conditions
- > Sharp Video Motion Images with Progressive Scanning
- > High Speed PTZ Dome with Privacy Masking, Two-way Audio and Built-in RS-485 Receiver/Driver
- > Synchronized IR LED & Fixed IR LED up to 450ft
- > 30x, 4.3 - 129mm, Auto-Focus, Optical Zoom Lens with 16x Digital Zoom Function
- > Triple streaming, 60-ips, H.264 and MJPEG Compression, 1080p Resolution
- > Define up to 240 Preset Camera Views that can be Recalled with a Simple Keyboard Command
- > Up to 8 Tours, each consisting of up to 100 Presets
- > View and Record up to 64 Cameras or View and Manage up to 64 NVR's, with included ATVision IP Remote Management Software
- > Pendant, Roof and Wall Mount Options Available
- > ONVIF Profile S Compliant for Network Video Interoperability
- > IP66 Rated Weatherproof and Impact Resistant Housing
- > 12VDC Power Source

SPECIFICATIONS

MODEL	IPSD302TWI
CAMERA	Image Sensor
	1/2.8" SONY Exmor CMOS
	Lens
	4.3mm ~ 129.0mm; 30x A/F Optical Zoom, 16x Digital Zoom
	Resolution Supported
	1920 x 1080p
	Scanning Mode
	Progressive Scan
	Min. Illumination
	Color: 0.5Lux, B/W: 0.1Lux
	AE/AWB
	Yes
	DNR
	Yes
	D&N
	True D&N (IR-cut filter)
NETWORK	WDR
	Yes
	DIS
	Yes
	BLC
	Yes
	Built-in IR
	Built in IR; Fixed IR LED, Synchronized IR LED; 450ft (150m)
	Pan Range
	360° Endless
	Pan Speed
	Preset: Max. 380°/sec, Manual: Max. 380°/sec
	Tilt Range
	180° (0° ~ 180°)
	Tilt Speed
	Preset: Max. 380°/sec, Manual: Max. 300°/sec
GENERAL	Preset
	240
	Progressive Encoding
	Yes
	Compression
	H.264 (BP/MP/HP), MJPEG
	Max. Frame Rate
	1080p@60/50fps, 1080p@30/25fps
	Multiple Streaming
	Triple Stream (2x H.264 and 1x MJPEG)
	Motion Detection
	Yes
	Event Buffering (Pre & Post)
	Yes
	Privacy Masking
	Yes
	PrVA (Pre-recorded Voice Alert)
	Yes (3 files)
	Cross Web Browser
	Yes
	FTP Image Upload
	Yes
	ONVIF Certificate
	Yes (Profile-S)
	Network Time Sync
	Yes
	Zero Configuration
	Yes
	Security
	Password Protection, IP Filtering, HTTPS, SSL
	Max. Connections
	10
	Protocols
	IPv4/IPv6, Manual, TCP/IP, UDP, HTTP, RTP, RTSP, NTP, DHCP, SMTP, DDMS, HTTPS, RTCP, FTP, Bonjour
	NAS Support
	Yes
	JPEG push
	Yes
	DDNS
	Yes
	Remote Client
	Web browser, SmartManager, ATVision IP
	Installation Tool
	SmartManager, ATVision IP
	Audio In/Out
	In x 1 / Out x 1 (G.711)
	Alarm In/Out
	In x 1 / Out x 1
	RS485
	RS485
	Ethernet
	10/100Mbps
	Weatherproof
	IP66
	Power
	12VDC \pm 10%
	Power Consumption
	3.0A (36W)
	Operating Temperature
	-22° ~ 122°F (-30° ~ 50°C)
	Operating Humidity
	0 ~ 90% RH
	External Dimension
	7.9 x 12in (201.8 x 305.3mm)
	Weight
	10.81lbs (4.9kg)
	Conformity Certifications
	FCC, CE, MIC


DIMENSIONS




ATVision IP Remote Management Software

ACCESSORIES

- DB241 Ceiling Mount
- DB242 Wall Mount
- PM304 Parapet Roof Mount
- SDK162J Keyboard Controller



DB242



DB241



PM304



SDK162J

Minimum System Requirements for ATVision IP Software

Operating System: Microsoft Windows 7 (or 8) Professional/ Enterprise/Ultimate

CPU: Intel Core i7; RAM: 4GB; Ethernet connection: 1Gbps

Graphics Card: Gaming rated, with 1GB at 1080p for Single Monitor; 2GB at 1080p for Multiple Monitors

HDD's: 7200RPM and 64MB cache; 1 separate HDD for Operating System and Software; and 1 (2TB) HDD for Recording (refer to IP storage calculator)