



## >>> REAL TIME FULL HD, 4ch, POE, NETWORK VIDEO RECORDER




### 4ch PoE NVR N04P

- > 4ch Network Video Recorder with H.264 Compression for Best-in-Class Recording and Storage Performance
- > Embedded PoE Switch for all Channels
- > Full HD (1920 x 1080) Real Time Recording of all Channels
- > ONVIF Profile S Compliant for Network Video Interoperability
- > Concurrent Full HD Display on HDMI and VGA Monitor Outputs
- > Powerful Pentaplex Functionality with Simultaneous Live, Recording, Playback, Backup and Network
- > Supports 1 Hard Disk Drive, 1 eSATA External Device, and Data Backup via USB 3.0
- > View and Manage an Unlimited Number of NVR Units and Record and Manage up to 64 Individual Cameras with the included ATVision IP Remote Management Software
- > Easy Plug and Play Functionality with Automatic Device Discovery and Display
- > IR Remote Control and USB Mouse Included
- > PTZ Camera Control via Network
- > Supports Mobile Phone Applications with Apple and Android Operating Systems

## SPECIFICATIONS

MODELS		N04P1 - 1TB N04P2 - 2TB
V I D E O	IP Camera Input	4
	Supported Video Format	H.264, MPEG-4, MJPEG
	Recording Video Resolution	320x240 ~ 2048 x 1536
	Recording Mode	Continuous, Schedule, Event, Network
	Recording Frame/Sec (FPS)	Max. 120fps @ 1920 x 1080; 80fps @ 2048 x 1536
	Search Mode	Calendar, Date / Time, Event, Protect, Capture, VCA
	Video Monitor Output	HDMI, VGA
	Monitor Resolution	1080p maximum
	Monitor Screen Modes	Full, Quad, PIP, Zoom
	N E T W O R K	Remote Mobile Support
Supported Protocol		TCP/IP, IPv4, HTTP, uPnP, DHCP, Zeroconfig, ONVIF v2.3 (Profile S)
Remote Access		ATVision IP Remote Management Software, Web Browser, Smart Manager
Web Browsers		IE, Chrome, Firefox
No. of simultaneous users		10
Remote Monitoring/Control		NAT Transversal and E-Map support
Throughput		6Mbps /Ch; 24Mbps Total
Internal HDD		Up to 1 SATA HDD's: 4TB Total Capacity
External HDD		Via 1 eSATA port : 16TB Total Capacity
Audio (In/Out)		4 (Ethernet) / 1 (RCA)
G E N E R A L	Alarm	Terminal TTL 4 Input, Terminal TTL 1 Output
	Ethernet	100/1000 Base-T (Gigabit)
	Ethernet PoE Switch	IEEE 802.3af
	Ethernet Ports	4 x RJ45 PoE Camera Ports; 1 x RJ45 Network Port
	HDMI Monitor Output	(Type A)
	VGA Monitor Output	(15-Pin D-Sub)
	USB	2 x USB2.0; 1 x USB3.0
	eSATA	1 e-SATA port
	Power Source	48VDC (Power Adapter & Cable included)
	Power Consumption	Max. 50W, w/four PoE Cameras; 20W w/ zero PoE Cameras
Operating Temperature	0°C ~ +45°C (+32°F ~ +114°F)	
Humidity	0%RH ~ 90%RH	
Dimension (W x H x D)	11.8 x 8.2 x 1.9in (300 x 227 x 53mm)	
Weight	2.2lbs (1.0kg) (without HDD)	
Conformity Certifications	FCC, CE (UL for Power Adapter Only)	


## DIMENSIONS



ATVision IP Remote Management Software

## ACCESSORIES

LB3S Recorder Lockbox  
eSATA Storage See eSATA External Storage Category



Rear Panel View

### Minimum System Requirements for ATVision IP Software

- Operating System: Microsoft Windows 7 (or 8) Professional/Enterprise/Ultimate
- CPU: Intel Core i7; RAM: 4GB; Ethernet connection: 1Gbps
- Graphics card: Gaming rated, with 1GB at 1080p for single monitor; 2GB at 1080p for multiple monitors
- HDD's: 7200RPM and 64MB cache; 1 separate HDD for operating system and software; and 1 (2TB) HDD for recording (refer to IP storage calculator)