

HDV2212MB


2MP HD ANALOG, VF LENS, VANDAL DOME CAMERA

- > 2.8-12mm Motorized Vari-focal Lens
- > High Definition Analog (HD Analog) over Coax Technology, utilizes existing Coax Cables & BNC Connectors, allowing Mega-pixel Video Images without any rewiring necessary
- > TVI, AHD and CVBS Protocol selectable --- Engineered to work with ATV's HD Analog and Legacy DVR's for Maximum Stability and Performance
- > ATVision IP Remote Management Client Software for Windows and Mac and Mobile Applications for Apple and Android Operating Systems are included



TECHNICAL SPECIFICATIONS

IMAGE Image Sensor 1/2.9" Sony Exmor CMOS: 2,000(H) x 1,121(V) Pixels Scanning Mode Progressive Video Resolution 1080p @ 25/30fps, (TVI & AHD); 1000TVL (CVBS) @ 30fps Min. Illumination 1.0Lux (Color), OLux (BW, IR LED On) IR 24 IR LED's (850nm); Max. 82ft indoor, 62ft outdoor S/N ratio More Than 50dB (AGC 0) FUNCTIONS Camera Control OSD (Joystick switch, Coaxial Communication) Lens 2.8-12mm F1.2, Motorized Vari-focal Shutter Auto, 1/30, 1/60, FLK~1/50,000sec AGC 1-15 Sens-Up Off/Auto (x2, x4, x6, x8, x10, x15, x20, x25, x30) Brightness 1-100 WDR - Digital Off/On/Auto Defog Off/Auto Backlight Off/BLC/HSBLC White Balance ATW/AWC/Indoor/Outdoor/Manual/AWB Day & Night Auto/Color/B&W DNR 2D / 3D D-Effect Off/Freeze/Mirror/Neg.Image Motion Detection Off/On (4 Zone) Privacy Masking Off/On (4 Zone) Sharpness	I COLLISTONE OF COL	II TOUITOIIO
Scanning Mode Progressive Video Resolution 1080p @ 25/30fps, (TVI & AHD); 1000TVL (CVBS) @ 30fps Min. Illumination 1.0Lux (Color), 0Lux (BW, IR LED On) IR 24 IR LED's (850nm); Max. 82ft indoor, 62ft outdoor S/N ratio More Than 50dB (AGC 0) FUNCTIONS Camera Control OSD (Joystick switch, Coaxial Communication) Lens 2.8~12mm F1.2, Motorized Vari-focal Shutter Auto, 1/30, 1/60, FLK~1/50,000sec AGC 1~15 Sens-Up Off/Auto (x2, x4, x6, x8, x10, x15, x20, x25, x30) Brightness 1~100 WDR - Digital Off/On/Auto Defog Off/Auto Backlight Off/BLC/HSBLC White Balance ATW/AWC/Indoor/Outdoor/Manual/AWB Day & Night Auto/Color/B&W DNR 2D / 3D D-Effect Off/Freeze/Mirror/Neg.Image Motion Detection Off/On (4 Zone) Sharpness Off/On (4 Zone) Sharpness Off/On (4 Zone) Sharpness Off/On (4 Zone) Sharpness Off	IMAGE	
Video Resolution 1080p @ 25/30fps, (TVI & AHD); 1000TVL (CVBS) @ 30fps Min. Illumination 1.0Lux (Color), 0Lux (BW, IR LED On) IR 24 IR LED's (850nm); Max. 82ft indoor, 62ft outdoor S/N ratio More Than 50dB (AGC 0) FUNCTIONS OSD (Joystick switch, Coaxial Communication) Lens 2.8~12mm F1.2, Motorized Vari-focal Shutter Auto, 1/30, 1/60, FLK~1/50,000sec AGC 1~15 Sens-Up Offf/Auto (x2, x4, x6, x8, x10, x15, x20, x25, x30) Brightness 1~10 WDR - Digital Off/On/Auto Defog Off/Auto Backlight Off/BLC/HSBLC White Balance ATW/AWC/Indoor/Outdoor/Manual/AWB Day & Night Auto/Color/B&W DNR 2D / 3D D-Effect Off/Freeze/Mirror/Neg.Image Motion Detection Off/On (4 Zone) Privacy Masking Off/On (4 Zone) Sharpness Off/Auto (0~10) GENERAL Video Output BNC Transmission Distance Coax Cable, RG6U (5C-2V), 1640ft (500m); RG59 (3C-2V), 984ft (300m) Operati	Image Sensor	1/2.9" Sony Exmor CMOS: 2,000(H) x 1,121(V) Pixels
Min. Illumination 1.0Lux (Color), 0Lux (BW, IR LED On) IR 24 IR LED's (850nm); Max. 82ft indoor, 62ft outdoor S/N ratio More Than 50dB (AGC 0) FUNCTIONS Camera Control OSD (Joystick switch, Coaxial Communication) Lens 2.8~12mm F1.2, Motorized Vari-focal Shutter Auto, 1/30, 1/60, FLK~1/50,000sec AGC 1~15 Sens-Up Off/Auto (x2, x4, x6, x8, x10, x15, x20, x25, x30) Brightness 1~100 WDR - Digital Off/On/Auto Defog Off/Auto Backlight Off/BLC/HSBLC White Balance ATW/AWC/Indoor/Outdoor/Manual/AWB Day & Night Auto/Color/B&W DNR 2D / 3D D-Effect Off/Freeze/Mirror/Neg.Image Motion Detection Off/On (4 Zone) Privacy Masking Off/On (4 Zone) Sharpness Off/Auto (0~10) GENERAL Video Output BNC Transmission Distance Coax Cable, RG6U (5C-2V), 1640ft (500m); RG59 (3C-2V), 984ft (300m) Operating Temperature -22°F ~ 140°F (-30°C ~ +60°C)	Scanning Mode	Progressive
R	Video Resolution	1080p @ 25/30fps, (TVI & AHD); 1000TVL (CVBS) @ 30fps
S/N ratio More Than 50dB (AGC 0) FUNCTIONS Camera Control OSD (Joystick switch, Coaxial Communication) Lens 2.8~12mm F1.2, Motorized Vari-focal Shutter Auto, 1/30, 1/60, FLK~1/50,000sec AGC 1~15 Sens-Up Off/Auto (x2, x4, x6, x8, x10, x15, x20, x25, x30) Brightness 1~100 WDR - Digital Off/On/Auto Defog Off/Auto Backlight Off/SBLC/HSBLC White Balance ATW/AWC/Indoor/Outdoor/Manual/AWB Day & Night Auto/Color/B&W DNR 2D / 3D D-Effect Off/Freeze/Mirror/Neg.Image Motion Detection Off/On (4 Zone) Privacy Masking Off/On (4 Zone) Sharpness Off/On (4 Zone) Sharpness Off/Auto (0~10) GENERAL Video Output BNC Transmission Distance Coax Cable, RG6U (5C-2V), 1640ft (500m); RG59 (3C-2V), 984ft (300m) Operating Temperature -22°F ~ 140°F (-30°C ~ +60°C) Operating Temperature -22°F ~ 140°F (-30°C ~ +60°C) Operati	Min. Illumination	
S/N ratio More Than 50dB (AGC 0) FUNCTIONS Camera Control OSD (Joystick switch, Coaxial Communication) Lens 2.8~12mm F1.2, Motorized Vari-focal Shutter Auto, 1/30, 1/60, FLK~1/50,000sec AGC 1~15 Sens-Up Off/Auto (x2, x4, x6, x8, x10, x15, x20, x25, x30) Brightness 1~100 WDR - Digital Off/On/Auto Defog Off/Auto Backlight Off/SBLC/HSBLC White Balance ATW/AWC/Indoor/Outdoor/Manual/AWB Day & Night Auto/Color/B&W DNR 2D / 3D D-Effect Off/Freeze/Mirror/Neg.Image Motion Detection Off/On (4 Zone) Privacy Masking Off/On (4 Zone) Sharpness Off/On (4 Zone) Sharpness Off/Auto (0~10) GENERAL Video Output BNC Transmission Distance Coax Cable, RG6U (5C-2V), 1640ft (500m); RG59 (3C-2V), 984ft (300m) Operating Temperature -22°F ~ 140°F (-30°C ~ +60°C) Operating Temperature -22°F ~ 140°F (-30°C ~ +60°C) Operati	IR	24 IR LED's (850nm); Max. 82ft indoor, 62ft outdoor
Camera Control OSD (Joystick switch, Coaxial Communication) Lens 2.8~12mm F1.2, Motorized Vari-focal Shutter Auto, 1/30, 1/60, FLK~1/50,000sec AGC 1~15 Sens-Up Off/Auto (x2, x4, x6, x8, x10, x15, x20, x25, x30) Brightness 1~100 WDR - Digital Off/On/Auto Defog Off/Auto Backlight Off/BLC/HSBLC White Balance ATW/AWC/Indoor/Outdoor/Manual/AWB Day & Night Auto/Color/B&W DNR 2D / 3D D-Effect Off/Freeze/Mirror/Neg.lmage Motion Detection Off/On (4 Zone) Privacy Masking Off/On (4 Zone) Sharpness Off/Auto (0~10) GENERAL Video Output BNC Transmission Distance Coax Cable, RG6U (5C-2V), 1640ft (500m); RG59 (3C-2V), 984ft (300m) Operating Temperature -22°F ~ 140°F (-30°C ~ +60°C) Operating Humidity 0~96% (Non-Condencing) Power Consumption Max. 4.5Watts (370mA) External Dimension Ø 5.67 x 3.85 in (Ø144 x 98 mm) Weight 1.17lb (S/N ratio	
Lens 2.8~12mm F1.2, Motorized Vari-focal Shutter Auto, 1/30, 1/60, FLK~1/50,000sec AGC 1~15 Sens-Up Off/Auto (x2, x4, x6, x8, x10, x15, x20, x25, x30) Brightness 1~100 WDR - Digital Off/On/Auto Defog Off/Auto Backlight Off/BLC/HSBLC White Balance ATW/AWC/Indoor/Outdoor/Manual/AWB Day & Night Auto/Color/B&W DNR 2D / 3D D-Effect Off/Freeze/Mirror/Neg.Image Motion Detection Off/On (4 Zone) Privacy Masking Off/On (4 Zone) Sharpness Off/Auto (0~10) GENERAL Video Output BNC Transmission Distance Coax Cable, RG6U (5C-2V), 1640ft (500m); RG59 (3C-2V), 984ft (300m) Operating Temperature -22°F ~ 140°F (-30°C ~ +60°C) Operating Humidity 0~96% (Non-Condencing) Power Source DC12V±10% Power Consumption Max. 4.5Watts (370mA) External Dimension Ø 5.67 x 3.85 in (Ø1444 x 98 mm) Weight 1.17lb (0.53kg)	FUNCTIONS	
Shutter Auto, 1/30, 1/60, FLK~1/50,000sec AGC 1~15 Sens-Up Off/Auto (x2, x4, x6, x8, x10, x15, x20, x25, x30) Brightness 1~100 WDR - Digital Off/On/Auto Defog Off/Auto Backlight Off/BLC/HSBLC White Balance ATW/AWC/Indoor/Outdoor/Manual/AWB Day & Night Auto/Color/B&W DNR 2D / 3D D-Effect Off/Freeze/Mirror/Neg.Image Motion Detection Off/On (4 Zone) Privacy Masking Off/On (4 Zone) Sharpness Off/Auto (0~10) GENERAL Video Output Video Output BNC Transmission Distance Coax Cable, RG6U (5C-2V), 1640ft (500m); RG59 (3C-2V), 984ft (300m) Operating Temperature -22°F ~ 140°F (-30°C ~ +60°C) Operating Humidity 0~96% (Non-Condencing) Power Source DC12V±10% Power Consumption Max. 4.5Watts (370mA) External Dimension Ø 5.67 x 3.85 in (Ø144 x 98 mm) Weight 1.171b (0.53kg)	Camera Control	OSD (Joystick switch, Coaxial Communication)
AGC 1~15 Sens-Up 0ff/Auto (x2, x4, x6, x8, x10, x15, x20, x25, x30) Brightness 1~100 WDR - Digital Off/On/Auto Defog Off/Auto Off/BLC/HSBLC White Balance ATW/AWC/Indoor/Outdoor/Manual/AWB Day & Night Auto/Color/B&W DNR 2D / 3D D-Effect Off/Freeze/Mirror/Neg.Image Motion Detection Off/On (4 Zone) Privacy Masking Off/On (4 Zone) Sharpness Off/Auto (0~10) GENERAL Video Output BNC Transmission Distance Coax Cable, RG6U (5C-2V), 1640ft (500m); RG59 (3C-2V), 984ft (300m) Operating Temperature -22°F ~ 140°F (-30°C ~ +60°C) Operating Humidity O~96% (Non-Condencing) Power Source DC12V±10% Power Consumption Max. 4.5Watts (370mA) External Dimension Ø 5.67 x 3.85 in (Ø144 x 98 mm) Weight 1.17lb (0.53kg) Environmental IP66, IK10	Lens	2.8~12mm F1.2, Motorized Vari-focal
Sens-Up Off/Auto (x2, x4, x6, x8, x10, x15, x20, x25, x30) Brightness 1~100 WDR - Digital Off/On/Auto Defog Off/Auto Backlight Off/BLC/HSBLC White Balance ATW/AWC/Indoor/Outdoor/Manual/AWB Day & Night Auto/Color/B&W DNR 2D / 3D D-Effect Off/Freeze/Mirror/Neg.Image Motion Detection Off/On (4 Zone) Privacy Masking Off/On (4 Zone) Sharpness Off/Auto (0~10) GENERAL Video Output BNC Transmission Distance Coax Cable, RG6U (5C-2V), 1640ft (500m); RG59 (3C-2V), 984ft (300m) Operating Temperature -22°F ~ 140°F (-30°C ~ +60°C) Operating Humidity 0~96% (Non-Condencing) Power Source DC12V±10% Power Consumption Max. 4.5Watts (370mA) External Dimension Ø 5.67 x 3.85 in (Ø1444 x 98 mm) Weight 1.17lb (0.53kg) Environmental IP66, IK10	Shutter	Auto, 1/30, 1/60, FLK~1/50,000sec
Brightness 1~100 WDR - Digital Off/On/Auto Defog Off/Auto Backlight Off/BLC/HSBLC White Balance ATW/AWC/Indoor/Outdoor/Manual/AWB Day & Night Auto/Color/B&W DNR 2D / 3D D-Effect Off/Freeze/Mirror/Neg.Image Motion Detection Off/On (4 Zone) Privacy Masking Off/On (4 Zone) Sharpness Off/Auto (0~10) GENERAL Video Output BNC Transmission Distance Coax Cable, RG6U (5C-2V), 1640ft (500m); RG59 (3C-2V), 984ft (300m) Operating Temperature -22°F ~ 140°F (-30°C ~ +60°C) Operating Humidity 0~96% (Non-Condencing) Power Source DC12V±10% Power Consumption Max. 4.5Watts (370mA) External Dimension Ø 5.67 x 3.85 in (Ø144 x 98 mm) Weight 1.17lb (0.53kg) Environmental IP66, IK10	AGC	1~15
WDR - Digital Off/On/Auto Defog Off/Auto Backlight Off/BLC/HSBLC White Balance ATW/AWC/Indoor/Outdoor/Manual/AWB Day & Night Auto/Color/B&W DNR 2D / 3D D-Effect Off/Freeze/Mirror/Neg.Image Motion Detection Off/On (4 Zone) Privacy Masking Off/On (4 Zone) Sharpness Off/Auto (0~10) GENERAL Video Output Video Output BNC Transmission Distance Coax Cable, RG6U (5C-2V), 1640ft (500m); RG59 (3C-2V), 984ft (300m) Operating Temperature -22°F ~ 140°F (-30°C ~ +60°C) Operating Humidity 0~96% (Non-Condencing) Power Source DC12V±10% Power Consumption Max. 4.5Watts (370mA) External Dimension Ø 5.67 x 3.85 in (Ø1444 x 98 mm) Weight 1.17lb (0.53kg) Environmental IP66, IK10	Sens-Up	Off/Auto (x2, x4, x6, x8, x10, x15, x20, x25, x30)
Defog Off/Auto Backlight Off/BLC/HSBLC White Balance ATW/AWC/Indoor/Outdoor/Manual/AWB Day & Night Auto/Color/B&W DNR 2D / 3D D-Effect Off/Freeze/Mirror/Neg.Image Motion Detection Off/On (4 Zone) Privacy Masking Off/On (4 Zone) Sharpness Off/Auto (0~10) GENERAL Video Output BNC Transmission Distance Coax Cable, RG6U (5C-2V), 1640ft (500m); RG59 (3C-2V), 984ft (300m) Operating Temperature -22°F ~ 140°F (-30°C ~ +60°C) Operating Humidity 0~96% (Non-Condencing) Power Source DC12V±10% Power Consumption Max. 4.5Watts (370mA) External Dimension Ø 5.67 x 3.85 in (Ø144 x 98 mm) Weight 1.17lb (0.53kg) Environmental IP66, IK10	Brightness	1~100
Backlight Off/BLC/HSBLC White Balance ATW/AWC/Indoor/Outdoor/Manual/AWB Day & Night Auto/Color/B&W DNR 2D / 3D D-Effect Off/Freeze/Mirror/Neg.Image Motion Detection Off/On (4 Zone) Privacy Masking Off/On (4 Zone) Sharpness Off/Auto (0~10) GENERAL Video Output BNC Transmission Distance Coax Cable, RG6U (5C-2V), 1640ft (500m); RG59 (3C-2V), 984ft (300m) Operating Temperature -22°F ~ 140°F (-30°C ~ +60°C) Operating Humidity 0~96% (Non-Condencing) Power Source DC12V±10% Power Consumption Max. 4.5Watts (370mA) External Dimension Ø 5.67 x 3.85 in (Ø144 x 98 mm) Weight 1.17lb (0.53kg) Environmental IP66, IK10	WDR - Digital	Off/On/Auto
White Balance ATW/AWC/Indoor/Outdoor/Manual/AWB Day & Night Auto/Color/B&W DNR 2D / 3D D-Effect Off/Freeze/Mirror/Neg.Image Motion Detection Off/On (4 Zone) Privacy Masking Off/On (4 Zone) Sharpness Off/Auto (0~10) GENERAL Video Output BNC Transmission Distance Coax Cable, RG6U (5C-2V), 1640ft (500m); RG59 (3C-2V), 984ft (300m) Operating Temperature -22°F ~ 140°F (-30°C ~ +60°C) Operating Humidity 0~96% (Non-Condencing) Power Source DC12V±10% Power Consumption Max. 4.5Watts (370mA) External Dimension Ø 5.67 x 3.85 in (Ø144 x 98 mm) Weight 1.17lb (0.53kg) Environmental IP66, IK10	Defog	Off/Auto
Day & Night Auto/Color/B&W DNR 2D / 3D D-Effect Off/Freeze/Mirror/Neg.Image Motion Detection Off/On (4 Zone) Privacy Masking Off/On (4 Zone) Sharpness Off/Auto (0~10) GENERAL BNC Transmission Distance Coax Cable, RG6U (5C-2V), 1640ft (500m); RG59 (3C-2V), 984ft (300m) Operating Temperature -22°F ~ 140°F (-30°C ~ +60°C) Operating Humidity 0~96% (Non-Condencing) Power Source DC12V±10% Power Consumption Max. 4.5Watts (370mA) External Dimension Ø 5.67 x 3.85 in (Ø144 x 98 mm) Weight 1.17lb (0.53kg) Environmental IP66, IK10	Backlight	Off/BLC/HSBLC
DNR 2D / 3D D-Effect Off/Freeze/Mirror/Neg.Image Motion Detection Off/On (4 Zone) Privacy Masking Off/On (4 Zone) Sharpness Off/Auto (0~10) GENERAL Video Output BNC Transmission Distance Coax Cable, RG6U (5C-2V), 1640ft (500m); RG59 (3C-2V), 984ft (300m) Operating Temperature -22°F ~ 140°F (-30°C ~ +60°C) Operating Humidity 0~96% (Non-Condencing) Power Source DC12V±10% Power Consumption Max. 4.5Watts (370mA) External Dimension Ø 5.67 x 3.85 in (Ø144 x 98 mm) Weight 1.17lb (0.53kg) Environmental IP66, IK10	White Balance	ATW/AWC/Indoor/Outdoor/Manual/AWB
D-Effect Off/Freeze/Mirror/Neg.Image Motion Detection Off/On (4 Zone) Privacy Masking Off/On (4 Zone) Sharpness Off/Auto (0~10) GENERAL Video Output BNC Transmission Distance Coax Cable, RG6U (5C-2V), 1640ft (500m); RG59 (3C-2V), 984ft (300m) Operating Temperature -22°F ~ 140°F (-30°C ~ +60°C) Operating Humidity 0~96% (Non-Condencing) Power Source DC12V±10% Power Consumption Max. 4.5Watts (370mA) External Dimension Ø 5.67 x 3.85 in (Ø144 x 98 mm) Weight 1.17lb (0.53kg) Environmental IP66, IK10	Day & Night	Auto/Color/B&W
Motion Detection Off/On (4 Zone) Privacy Masking Off/On (4 Zone) Sharpness Off/Auto (0~10) GENERAL Video Output BNC Transmission Distance Coax Cable, RG6U (5C-2V), 1640ft (500m); RG59 (3C-2V), 984ft (300m) Operating Temperature -22°F ~ 140°F (-30°C ~ +60°C) Operating Humidity 0~96% (Non-Condencing) Power Source DC12V±10% Power Consumption Max. 4.5Watts (370mA) External Dimension Ø 5.67 x 3.85 in (Ø144 x 98 mm) Weight 1.17lb (0.53kg) Environmental IP66, IK10	DNR	2D / 3D
Privacy Masking Off/On (4 Zone) Sharpness Off/Auto (0~10) GENERAL Video Output BNC Transmission Distance Coax Cable, RG6U (5C-2V), 1640ft (500m); RG59 (3C-2V), 984ft (300m) Operating Temperature -22°F ~ 140°F (-30°C ~ +60°C) Operating Humidity 0~96% (Non-Condencing) Power Source DC12V±10% Power Consumption Max. 4.5Watts (370mA) External Dimension Ø 5.67 x 3.85 in (Ø144 x 98 mm) Weight 1.17lb (0.53kg) Environmental IP66, IK10	D-Effect	Off/Freeze/Mirror/Neg.Image
Sharpness Off/Auto (0~10) GENERAL Video Output BNC Transmission Distance Coax Cable, RG6U (5C-2V), 1640ft (500m); RG59 (3C-2V), 984ft (300m) Operating Temperature -22°F ~ 140°F (-30°C ~ +60°C) Operating Humidity 0~96% (Non-Condencing) Power Source DC12V±10% Power Consumption Max. 4.5Watts (370mA) External Dimension Ø 5.67 x 3.85 in (Ø144 x 98 mm) Weight 1.17lb (0.53kg) Environmental IP66, IK10	Motion Detection	Off/On (4 Zone)
GENERAL Video Output BNC Transmission Distance Coax Cable, RG6U (5C-2V), 1640ft (500m); RG59 (3C-2V), 984ft (300m) Operating Temperature -22°F ~ 140°F (-30°C ~ +60°C) Operating Humidity 0~96% (Non-Condencing) Power Source DC12V±10% Power Consumption Max. 4.5Watts (370mA) External Dimension Ø 5.67 x 3.85 in (Ø144 x 98 mm) Weight 1.17lb (0.53kg) Environmental IP66, IK10	Privacy Masking	Off/On (4 Zone)
Video Output BNC Transmission Distance Coax Cable, RG6U (5C-2V), 1640ft (500m); RG59 (3C-2V), 984ft (300m) Operating Temperature -22°F ~ 140°F (-30°C ~ +60°C) Operating Humidity 0~96% (Non-Condencing) Power Source DC12V±10% Power Consumption Max. 4.5Watts (370mA) External Dimension Ø 5.67 x 3.85 in (Ø144 x 98 mm) Weight 1.17lb (0.53kg) Environmental IP66, IK10	Sharpness	Off/Auto (0~10)
Transmission Distance Coax Cable, RG6U (5C-2V), 1640ft (500m); RG59 (3C-2V), 984ft (300m) Operating Temperature -22°F ~ 140°F (-30°C ~ +60°C) Operating Humidity 0~96% (Non-Condencing) Power Source DC12V±10% Power Consumption Max. 4.5Watts (370mA) External Dimension Ø 5.67 x 3.85 in (Ø144 x 98 mm) Weight 1.17lb (0.53kg) Environmental IP66, IK10	GENERAL	
Operating Temperature -22°F ~ 140°F (-30°C ~ +60°C) Operating Humidity 0~96% (Non-Condencing) Power Source DC12V±10% Power Consumption Max. 4.5Watts (370mA) External Dimension Ø 5.67 x 3.85 in (Ø144 x 98 mm) Weight 1.17lb (0.53kg) Environmental IP66, IK10	Video Output	
Operating Humidity 0~96% (Non-Condencing) Power Source DC12V±10% Power Consumption Max. 4.5Watts (370mA) External Dimension Ø 5.67 x 3.85 in (Ø144 x 98 mm) Weight 1.17lb (0.53kg) Environmental IP66, IK10	Transmission Distance	Coax Cable, RG6U (5C-2V), 1640ft (500m); RG59 (3C-2V), 984ft (300m)
Power Source DC12V±10% Power Consumption Max. 4.5Watts (370mA) External Dimension Ø 5.67 x 3.85 in (Ø144 x 98 mm) Weight 1.17lb (0.53kg) Environmental IP66, IK10	Operating Temperature	-22°F ~ 140°F (-30°C ~ +60°C)
Power Consumption Max. 4.5Watts (370mA) External Dimension Ø 5.67 x 3.85 in (Ø144 x 98 mm) Weight 1.17lb (0.53kg) Environmental IP66, IK10	Operating Humidity	
External Dimension Ø 5.67 x 3.85 in (Ø144 x 98 mm) Weight 1.17lb (0.53kg) Environmental IP66, IK10	Power Source	DC12V±10%
Weight 1.17lb (0.53kg) Environmental IP66, IK10	Power Consumption	Max. 4.5Watts (370mA)
Environmental IP66, IK10	External Dimension	Ø 5.67 x 3.85 in (Ø144 x 98 mm)
· · · · · · · · · · · · · · · · · · ·		
Conformity Certifications FCC, CE, UL	Environmental	IP66, IK10
	Conformity Certifications	FCC, CE, UL



ACCESSORIES

HDB243XB Wall Mount
HDA502B Junction Box
HDB453B Pendant Mount
HPDA3B Pendant Cap

