



NFE5360

5MP IP, FISHEYE INDOOR CAMERA

- > Ultra-wide angle 1.05mm, 360° Panoramic Lens
- > Exceptional 5MP, 2592 x 1944 Resolution, Video Images
- > Multiple Display Modes: 90°, 180° & 360°
- > ATVision IP Remote Management Client Software for Windows and Mac and Mobile Applications for Apple and Android Operating Systems are included

TECHNICAL SPECIFICATIONS

IMAGE	
Image Sensor	Type : 1/1.8" SONY Starvis CMOS Sensor Pixels : 3096(H) x 2080(V)
Min. Illumination	Color : 0.3Lux / BW : 0.07Lux @F2.8, 50IRE
Scanning Mode	Progressive Scan
Resolution	2592 x 1944 ~ 480 x 480; @ 12.5/15fps
FUNCTIONS	
Lens / Angle of View	Fixed 1.05mm, F2.8 / 180° (H)
Wide Dynamic Range	D-WDR (ATR-EX)
Day and Night Mode	True D/N (Auto, Day, Night)
Noise Reduction	3DNR
Image Effect	Flip, Mirror, Aisle, Defog, HLC, BLC, Digital Zoom, White Balance
Shutter Speed	Auto (1/10,000~1sec), Manual
Compression	H.264 (Baseline, Main, High Profile), MJPEG
Streaming	Triple Stream : H.264 x 2, MJPEG x 1
Audio	G.711; 2 Way
VMD / Privacy	16 Areas / 8 Zones
Event Notification	E-mail, FTP, Notification Server, XML Notification, AIHM
Security	Multi User Authority, IP Filtering, HTTPS, SSL
Network Time Sync	NTP Server, Synchronized Computer, Manual
Remote Upgrade	Web Browsing (IE, Chrome, Safari, Firefox), SmartManager
SD Recording Mode	Event, Continuous
NETWORK	
Protocol	TCP/IP, UDP, IPv4/v6, HTTP, HTTPS, QoS, FTP, UPnP, RTP, RTSP, RTCP, DHCP, ARP, Zeroconf, Bonjour
Client Software & Users	ATVision IP CMS & Mobile; Max Live Users: 10; Playback Users: 3
API Support	Open API, Onvif Compliance
GENERAL	
Audio / Alarm	1 Input, 1 Output (Terminal Block) / 1 Input, 1 Output (Terminal Block)
Ethernet	RJ-45 (10/100Base-T)
SD Card Slot	SDHC, SDXC (128GB)
Operating Temp & Humidity	14~122°F (-10~+50°C); 0~90% RH (Non-Condensing)
Power Source	PoE (IEEE802.3af) / 12VDC; 110mA (5.3W) @PoE / 400mA (4.8W) @12VDC
Dimensions & Weight	Ø 4.7 x 2.5in (Ø 119 x 63.8mm); 0.6lb (0.27kg)
Conformity Certifications	FCC, CE, UL



ACCESSORIES

HDB344 Wall Mount