

# NVR32P4

## 32сн, 16 PoE, 4K RESOLUTION, H.265 NVR

- > H.265 Compression for Best-in-Class Recording and Storage
- > 4ch Recording up to 4K (8MP) Resolution Images
- > Concurrent Display on HDMI and VGA Monitor Outputs
- > Embedded PoE Switch for 16 Video Channels
- > 4 SATA HDD Bays






# **ACCESSORIES**

LB3L Recorder Lockbox; Black

#### **MODELS**

| NVR32P48T  | 8TB HDD  |
|------------|----------|
| NVR32P412T | 12TB HDD |
| NVR32P416T | 16TB HDD |
| NVR32P418T | 18TB HDD |
| NVR32P420T | 20TB HDD |
| NVR32P424T | 24TB HDD |
| NVR32P432T | 32TB HDD |
|            |          |

Rear View



## TECHNICAL SPECIFICATIONS

| Video Input   32 IP, up to 4K (8MP)  | VIDEO                     |  |  |
|--|---------------------------|--|--|
| Display Mode RECORDING Compression H.264, H.265 Recording Speed 800 / 960fps @ 8MP Max. Recording 256Mbps Recording Mode Continuous, Motion, Alarm, C+M, C+A, M+A, C+M+A, Panic Pre / Post Alarm PLAYBACK Simultaneous Playback Playback Mode Backward, Forward 2~64x Search Mode Time, Event, Thumbnail, Text, Smart (Motion) NETWORK Ethernet WAN: 1 R,145 10/100/1000 Base-T PoE: 16 R,145 10/100 Base-T PoE: 16 R,145 10/100 Base-T PoE Power: 130W(IEEE802.3at Compliance) Unlimited (Guarantee 576Mbps, Support Bandwidth Control) Remote Monitoring Web, ATVision IP CMS & Mobile Apps GENERAL Text In POS/ATM (ASCII, Network) Internal HDD 4 SATA up to 12TB each, total 48TB Backup USB: AVI, H4V, MP4 File Formats Audio 1 R CA Input / 1 RCA Output Alarm 16 Input / 1 Output (Terminal Block) USB 2 USB2.0, 1 USB3.0 Rack Mountable Operating Humidity O~90% RH (Non-Condensing) Operating Temperature 32°~114°F (O~+45°C) Power Consumption 35W (with 2 HDD) Dimension(WXHXD) 17.2 x 3.5 x 14in (435.7 x 88.7 x 356mm) Net Weight Playback HA.264, H.265 RMP MMP4, H.264, M.44, MP4 DD) Poinension(WXHXD) 17.2 x 3.5 x 14in (435.7 x 88.7 x 356mm) Net Weight Playback HA.265 RAMP  Alarm, C+M, C+A, M+A, C+M, A, M+A, C+M+A, C+M | Video Input               | 32 IP, up to 4K (8MP)                                  |  |
| Recording Speed   B00 / 960fps @ 8MP   | Display Output            | 1 VGA, 1 HDMI; 3840x2160 ~ 1024x768 @ 800 / 960fps     |  |
| Compression H.264, H.265 Recording Speed 800 / 960fps @ 8MP  Max. Recording 256Mbps Recording Mode Continuous, Motion, Alarm, C+M, C+A, M+A, C+M+A, Panic Pre / Post Alarm 1~5sec / 5sec~1hour  PLAYBACK Simultaneous Playback   1 / 4 / 9 / 16 / 32 Split Playback Mode Backward, Forward 2~64x Search Mode Time, Event, Thumbnail, Text, Smart (Motion)  NETWORK Ethernet WAN: 1 RJ45 10/100/1000 Base-T Pof: 16 RJ45 10/100 Base-T Pof: 16 RJ45 10/100 Base-T Pof: 19 Power: 130W(IEEE802.3at Compliance)  Max. Output Throughput Unlimited (Guarantee 576Mbps, Support Bandwidth Control) Remote Monitoring Web, ATVision IP CMS & Mobile Apps  GENERAL Text In POS/ATM (ASCII, Network) Internal HDD 4 SATA up to 12TB each, total 48TB Backup USB: AVI, H4V, MP4 File Formats  Audio 1 RCA Input / 1 RCA Output Alarm 16 Input / 1 Output (Terminal Block)  USB 2 USB2.0, 1 USB3.0  Rack Mountable Rack Ears Included Operating Humidity 0~90% RH (Non-Condensing) Operating Temperature 32°-114°F (0~+45°C) Power Consumption 35W (with 2 HDD) Dimension(WXHXD) 17.2 x 3.5 x 14in (435.7 x 88.7 x 356mm) Net Weight 9.9lb (4.5kg) (without HDD)   | Display Mode              | 1 / 4 / 9 / 16 / 32 Split, Sequence, PIP               |  |
| Recording Speed 800 / 960fps @ 8MP  Max. Recording 256Mbps Recording Mode Continuous, Motion, Alarm, C+M, C+A, M+A, C+M+A, Panic Pre / Post Alarm 1~5sec / 5sec~1hour PLAYBACK Simultaneous Playback 1 / 4 / 9 / 16 / 32 Split Playback Mode Backward, Forward 2~64x Search Mode Time, Event, Thumbnail, Text, Smart (Motion)  NETWORK Ethernet WAN: 1 RJ45 10/100/1000 Base-T POE: 16 RJ45 10/100 Base-T POE: 16 RJ45 10/100 Base-T POE Power: 130W(IEEE802.3at Compliance)  Max. Output Throughput Unlimited (Guarantee 576Mbps, Support Bandwidth Control)  Web, ATVision IP CMS & Mobile Apps  GENERAL  Text In POS/ATM (ASCII, Network) Internal HDD 4 SATA up to 12TB each, total 48TB Backup USB: AVI, H4V, MP4 File Formats  Audio 1 RCA Input / 1 RCA Output Alarm 16 Input / 1 Output (Terminal Block)  Serial Port 1 RS485 (Terminal Block)  USB 2 USB2.0, 1 USB3.0  Rack Mountable Rack Ears Included Operating Humidity 0~90% RH (Non-Condensing) Operating Temperature 32°~114°F (0~+45°C) Power Consumption 35W (with 2 HDD) Dimension(WxHxD) 17.2 x 3.5 x 14in (435.7 x 88.7 x 356mm) Net Weight 9.9lb (4.5kg) (without HDD)   |                           |  |  |
| Max. Recording Recording Mode Continuous, Motion, Alarm, C+M, C+A, M+A, C+M+A, Panic Pre / Post Alarm PLAYBACK Simultaneous Playback Search Mode Backward, Forward 2~64x Search Mode Time, Event, Thumbnail, Text, Smart (Motion) NETWORK Ethernet WAN: 1 RJ45 10/100/1000 Base-T PoE: 16 RJ45 10/100 Base-T PoE Power: 130W(IEEE802.3at Compliance) Max. Output Throughput Unlimited (Guarantee 576Mbps, Support Bandwidth Control) Remote Monitoring Web, ATVision IP CMS & Mobile Apps GENERAL Text In POS/ATM (ASCII, Network) Internal HDD 4 SATA up to 12TB each, total 48TB Backup USB: AVI, H4V, MP4 File Formats Audio 1 RCA Input / 1 RCA Output Alarm 16 Input / 1 Output (Terminal Block) Serial Port 1 RS485 (Terminal Block) USB 2 USB2.0, 1 USB3.0 Rack Mountable Operating Humidity O~90% RH (Non-Condensing) Operating Temperature 32°~114°F (O~+45°C) Power Consumption Dimension(WxHxD) 17.2 x 3.5 x 14in (435.7 x 88.7 x 356mm) Net Weight PAX  Spilt  Net Weight  1 ~4 / 9 / 16 / 32 Split Pohl, C+M, C+M, M+A, C+M, M+A, C+M+A, M+A, C+M+A, M+A, C+M+A, M+A, C+M+A, M+A, C+M+A, M+A, M+A, M+A, M+A, M+A, M+A, M+A,   | Compression               | H.264, H.265   |  |
| Recording Mode Continuous, Motion, Alarm, C+M, C+A, M+A, C+M+A, Panic Pre / Post Alarm PLAYBACK Simultaneous Playback   1 / 4 / 9 / 16 / 32 Split Playback Mode   Backward, Forward 2~64x Search Mode   Time, Event, Thumbnail, Text, Smart (Motion) NETWORK Ethernet   WAN: 1 RJ45 10/100/1000 Base-T PoE : 16 RJ45 10/100 Base-T PoE : 90 Power : 130W(IEE802.3at Compliance) Unlimited (Guarantee 576Mbps, Support Bandwidth Control) Remote Monitoring   Web, ATVision IP CMS & Mobile Apps GENERAL Text In   POS/ATM (ASCII, Network) Internal HDD   4 SATA up to 12TB each, total 48TB Backup   USB: AVI, H4V, M4 File Formats Audio   1 RCA Input / 1 RCA Output Alarm   16 Input / 1 Output (Terminal Block) USB   2 USB2.0, 1 USB3.0 Rack Mountable   Rack Ears Included Operating Humidity   0~90% RH (Non-Condensing) Operating Temperature   32°~114°F (0~+45°C) Power Consumption   35W (with 2 HDD) Dimension(WXHXD)   17.2 x 3.5 x 14in (435.7 x 88.7 x 356mm) Net Weight   9.9lb (4.5kg) (without HDD)   | Recording Speed           | 800 / 960fps @ 8MP                                     |  |
| Pre / Post Alarm PLAYBACK  Simultaneous Playback Playback Mode Backward, Forward 2~64x Search Mode NETWORK  Ethernet WAN: 1 RJ45 10/100/1000 Base-T PoE: 16 RJ45 10/100 Base-T PoE : 16 RJ45 10/100 Base-T PoE Power: 130W(IEEE802.3at Compliance)  Max. Output Throughput Unlimited (Guarantee 576Mbps, Support Bandwidth Control) Remote Monitoring Web, ATVision IP CMS & Mobile Apps  GENERAL  Text In POS/ATM (ASCII, Network) Internal HDD 4 SATA up to 12TB each, total 48TB Backup USB: AVI, H4V, MP4 File Formats Audio 1 RCA Input / 1 RCA Output Alarm 16 Input / 1 Output (Terminal Block)  Serial Port 1 RS485 (Terminal Block) USB 2 USB2.0, 1 USB3.0 Rack Mountable Operating Humidity O~90% RH (Non-Condensing) Operating Temperature 32°~114°F (O~+45°C) Power Supply Power Consumption 35W (with 2 HDD) Dimension(WxHxD) 17.2 x 3.5 x 14in (435.7 x 88.7 x 356mm) Net Weight   | Max. Recording            | 256Mbps  |  |
| Simultaneous Playback Simultaneous Playback Playback Mode Backward, Forward 2~64x Search Mode NETWORK Ethernet WAN: 1 RJ45 10/100/1000 Base-T PoE: 16 RJ45 10/100 Base-T PoE Power: 130W(IEEE802.3at Compliance) Wax. Output Throughput Unlimited (Guarantee 576Mbps, Support Bandwidth Control) Remote Monitoring Web, ATVision IP CMS & Mobile Apps GENERAL Text In POS/ATM (ASCII, Network) Internal HDD 4 SATA up to 12TB each, total 48TB Backup USB: AVI, H4V, MP4 File Formats Audio 1 RCA Input / 1 RCA Output Alarm 16 Input / 1 Output (Terminal Block) Serial Port 1 RS485 (Terminal Block) USB 2 USB2.0, 1 USB3.0 Rack Mountable Rack Ears Included Operating Humidity O~90% RH (Non-Condensing) Operating Temperature 32°~114°F (O~+45°C) Power Supply Power Consumption Jimension(WxHxD) Net Weight 9.9lb (4.5kg) (without HDD)  | Recording Mode            | Continuous, Motion, Alarm, C+M, C+A, M+A, C+M+A, Panic |  |
| Simultaneous Playback   1 / 4 / 9 / 16 / 32 Split   Playback Mode   Backward, Forward 2~64x   Search Mode   Time, Event, Thumbnail, Text, Smart (Motion)   NETWORK   Ethernet   WAN: 1 RJ45 10/100/1000 Base-T   POE: 16 RJ45 10/100 Base-T   POE: 16 RJ | Pre / Post Alarm          | 1~5sec / 5sec~1hour                                    |  |
| Playback Mode Search Mode Time, Event, Thumbnail, Text, Smart (Motion)  NETWORK  Ethernet WAN: 1 RJ45 10/100/1000 Base-T POE: 16 RJ45 10/100 Base-T POE: 16 RJ45 10/100 Base-T PoE Power: 130W(IEEE802.3at Compliance)  Max. Output Throughput Unlimited (Guarantee 576Mbps, Support Bandwidth Control)  Remote Monitoring Web, ATVision IP CMS & Mobile Apps  GENERAL  Text In POS/ATM (ASCII, Network) Internal HDD 4 SATA up to 12TB each, total 48TB  Backup USB: AVI, H4V, MP4 File Formats  Audio 1 RCA Input / 1 RCA Output  Alarm 16 Input / 1 Output (Terminal Block)  Serial Port 1 RS485 (Terminal Block)  USB 2 USB2.0, 1 USB3.0  Rack Mountable Rack Ears Included Operating Humidity 0~90% RH (Non-Condensing) Operating Temperature 32°~114°F (0~+45°C) Power Supply 100 - 220VAC  Power Consumption 35W (with 2 HDD) Dimension(WxHxD) 17.2 x 3.5 x 14in (435.7 x 88.7 x 356mm) Net Weight  | PLAYBACK                  |  |  |
| Search Mode NETWORK  Ethernet WAN: 1 RJ45 10/100/1000 Base-T POE: 16 RJ45 10/100 Base-T POE POwer: 130W(IEEE802.3at Compliance)  Max. Output Throughput Unlimited (Guarantee 576Mbps, Support Bandwidth Control)  Remote Monitoring Web, ATVision IP CMS & Mobile Apps  GENERAL  Text In POS/ATM (ASCII, Network) Internal HDD 4 SATA up to 12TB each, total 48TB  Backup USB: AVI, H4V, MP4 File Formats  Audio 1 RCA Input / 1 RCA Output  Alarm 16 Input / 1 Output (Terminal Block)  Serial Port 1 RS485 (Terminal Block) USB 2 USB2.0, 1 USB3.0  Rack Mountable Qperating Humidity 0~90% RH (Non-Condensing) Operating Temperature 32°~114°F (0~+45°C) Power Supply 100 - 220VAC Power Consumption Jimension(WxHxD) 17.2 x 3.5 x 14in (435.7 x 88.7 x 356mm) Net Weight 9.9lb (4.5kg) (without HDD)   | Simultaneous Playback     | 1 / 4 / 9 / 16 / 32 Split                              |  |
| Ethernet  WAN: 1 RJ45 10/100/1000 Base-T POE: 16 RJ45 10/100 Base-T POE Power: 130W(IEEE802.3at Compliance)  Max. Output Throughput Remote Monitoring Web, ATVision IP CMS & Mobile Apps  GENERAL  Text In POS/ATM (ASCII, Network) Internal HDD 4 SATA up to 12TB each, total 48TB Backup USB: AVI, H4V, MP4 File Formats Audio 1 RCA Input / 1 RCA Output Alarm 16 Input / 1 Output (Terminal Block) Serial Port 1 RS485 (Terminal Block) USB 2 USB2.0, 1 USB3.0 Rack Mountable Rack Ears Included Operating Humidity O~90% RH (Non-Condensing) Operating Temperature 32°~114°F (0~+45°C) Power Consumption 35W (with 2 HDD) Dimension(WxHxD) 17.2 x 3.5 x 14in (435.7 x 88.7 x 356mm) Net Weight  | Playback Mode             | Backward, Forward 2~64x                                |  |
| Ethernet  WAN: 1 RJ45 10/100/1000 Base-T POE: 16 RJ45 10/100 Base-T POE Power: 130W(IEEE802.3at Compliance)  Max. Output Throughput Unlimited (Guarantee 576Mbps, Support Bandwidth Control) Web, ATVision IP CMS & Mobile Apps  GENERAL  Text In POS/ATM (ASCII, Network) Internal HDD 4 SATA up to 12TB each, total 48TB Backup USB: AVI, H4V, MP4 File Formats Audio 1 RCA Input / 1 RCA Output Alarm 16 Input / 1 Output (Terminal Block) Serial Port 1 RS485 (Terminal Block) USB 2 USB2.0, 1 USB3.0 Rack Mountable Rack Ears Included Operating Humidity O~90% RH (Non-Condensing) Operating Temperature 32°~114°F (0~+45°C) Power Consumption 35W (with 2 HDD) Dimension(WxHxD) 17.2 x 3.5 x 14in (435.7 x 88.7 x 356mm) Net Weight   | Search Mode               | Time, Event, Thumbnail, Text, Smart (Motion)           |  |
| PoE: 16 RJ45 10/100 Base-T PoE Power: 130W(IEEE802.3at Compliance)  Max. Output Throughput Unlimited (Guarantee 576Mbps, Support Bandwidth Control)  Remote Monitoring Web, ATVision IP CMS & Mobile Apps  GENERAL  Text In POS/ATM (ASCII, Network) Internal HDD 4 SATA up to 12TB each, total 48TB  Backup USB: AVI, H4V, MP4 File Formats  Audio 1 RCA Input / 1 RCA Output  Alarm 16 Input / 1 Output (Terminal Block)  Serial Port 1 RS485 (Terminal Block)  USB 2 USB2.0, 1 USB3.0  Rack Mountable Rack Ears Included  Operating Humidity 0~90% RH (Non-Condensing)  Operating Temperature 32°~114°F (0~+45°C)  Power Consumption 35W (with 2 HDD)  Dimension(WxHxD) 17.2 x 3.5 x 14in (435.7 x 88.7 x 356mm)  Net Weight  | NETWORK                   |  |  |
| PoE Power: 130W(IEEE802.3at Compliance)  Max. Output Throughput Unlimited (Guarantee 576Mbps, Support Bandwidth Control)  Remote Monitoring Web, ATVision IP CMS & Mobile Apps  GENERAL  Text In POS/ATM (ASCII, Network)  Internal HDD 4 SATA up to 12TB each, total 48TB  Backup USB: AVI, H4V, MP4 File Formats  Audio 1 RCA Input / 1 RCA Output  Alarm 16 Input / 1 Output (Terminal Block)  Serial Port 1 RS485 (Terminal Block)  USB 2 USB2.0, 1 USB3.0  Rack Mountable Rack Ears Included  Operating Humidity 0-90% RH (Non-Condensing)  Operating Temperature 32°~114°F (0~+45°C)  Power Supply 100 - 220VAC  Power Consumption 35W (with 2 HDD)  Dimension(WxHxD) 17.2 x 3.5 x 14in (435.7 x 88.7 x 356mm)  Net Weight   | Ethernet                  |  |  |
| Max. Output Throughput Unlimited (Guarantee 576Mbps, Support Bandwidth Control)  Remote Monitoring Web, ATVision IP CMS & Mobile Apps  GENERAL  Text In POS/ATM (ASCII, Network)  Internal HDD 4 SATA up to 12TB each, total 48TB  Backup USB: AVI, H4V, MP4 File Formats  Audio 1 RCA Input / 1 RCA Output  Alarm 16 Input / 1 Output (Terminal Block)  Serial Port 1 RS485 (Terminal Block)  USB 2 USB2.0, 1 USB3.0  Rack Mountable Rack Ears Included  Operating Humidity 0-90% RH (Non-Condensing)  Operating Temperature 32°~114°F (0~+45°C)  Power Supply 100 - 220VAC  Power Consumption 35W (with 2 HDD)  Dimension(WxHxD) 17.2 x 3.5 x 14in (435.7 x 88.7 x 356mm)  Net Weight 9.9lb (4.5kg) (without HDD)  |                           |  |  |
| Remote Monitoring Web, ATVision IP CMS & Mobile Apps  GENERAL  Text In POS/ATM (ASCII, Network)  Internal HDD 4 SATA up to 12TB each, total 48TB  Backup USB: AVI, H4V, MP4 File Formats  Audio 1 RCA Input / 1 RCA Output  Alarm 16 Input / 1 Output (Terminal Block)  Serial Port 1 RS485 (Terminal Block)  USB 2 USB2.0, 1 USB3.0  Rack Mountable Rack Ears Included  Operating Humidity 0~90% RH (Non-Condensing)  Operating Temperature 32°~114°F (0~+45°C)  Power Supply 100 - 220VAC  Power Consumption 35W (with 2 HDD)  Dimension(WxHxD) 17.2 x 3.5 x 14in (435.7 x 88.7 x 356mm)  Net Weight 9.9lb (4.5kg) (without HDD)   | Mary Ordered Theory about |  |  |
| GENERAL           Text In         POS/ATM (ASCII, Network)           Internal HDD         4 SATA up to 12TB each, total 48TB           Backup         USB: AVI, H4V, MP4 File Formats           Audio         1 RCA Input / 1 RCA Output           Alarm         16 Input / 1 Output (Terminal Block)           Serial Port         1 RS485 (Terminal Block)           USB         2 USB2.0, 1 USB3.0           Rack Mountable         Rack Ears Included           Operating Humidity         0~90% RH (Non-Condensing)           Operating Temperature         32°~114°F (0~+45°C)           Power Supply         100 - 220VAC           Power Consumption         35W (with 2 HDD)           Dimension(WxHxD)         17.2 x 3.5 x 14in (435.7 x 88.7 x 356mm)           Net Weight         9.9lb (4.5kg) (without HDD)   |                           |  |  |
| Text In POS/ATM (ASCII, Network) Internal HDD 4 SATA up to 12TB each, total 48TB Backup USB: AVI, H4V, MP4 File Formats Audio 1 RCA Input / 1 RCA Output Alarm 16 Input / 1 Output (Terminal Block) Serial Port 1 RS485 (Terminal Block) USB 2 USB2.0, 1 USB3.0 Rack Mountable Rack Ears Included Operating Humidity 0~90% RH (Non-Condensing) Operating Temperature 32°~114°F (0~+45°C) Power Supply 100 - 220VAC Power Consumption 35W (with 2 HDD) Dimension(WxHxD) 17.2 x 3.5 x 14in (435.7 x 88.7 x 356mm) Net Weight 9.9lb (4.5kg) (without HDD)   | Ü                         | Web, ATVISION IP CIVIS & IVIODITE APPS                 |  |
| Internal HDD 4 SATA up to 12TB each, total 48TB Backup USB: AVI, H4V, MP4 File Formats Audio 1 RCA Input / 1 RCA Output Alarm 16 Input / 1 Output (Terminal Block) Serial Port 1 RS485 (Terminal Block) USB 2 USB2.0, 1 USB3.0 Rack Mountable Rack Ears Included Operating Humidity 0~90% RH (Non-Condensing) Operating Temperature 32°~114°F (0~+45°C) Power Supply 100 - 220VAC Power Consumption 35W (with 2 HDD) Dimension(WxHxD) 17.2 x 3.5 x 14in (435.7 x 88.7 x 356mm) Net Weight 9.9lb (4.5kg) (without HDD)  |                           |  |  |
| Backup USB: AVI, H4V, MP4 File Formats  Audio 1 RCA Input / 1 RCA Output  Alarm 16 Input / 1 Output (Terminal Block)  Serial Port 1 RS485 (Terminal Block)  USB 2 USB2.0, 1 USB3.0  Rack Mountable Rack Ears Included  Operating Humidity 0~90% RH (Non-Condensing)  Operating Temperature 32°~114°F (0~+45°C)  Power Supply 100 - 220VAC  Power Consumption 35W (with 2 HDD)  Dimension(WxHxD) 17.2 x 3.5 x 14in (435.7 x 88.7 x 356mm)  Net Weight 9.9lb (4.5kg) (without HDD)   |                           |  |  |
| Audio         1 RCA Input / 1 RCA Output           Alarm         16 Input / 1 Output (Terminal Block)           Serial Port         1 RS485 (Terminal Block)           USB         2 USB2.0, 1 USB3.0           Rack Mountable         Rack Ears Included           Operating Humidity         0~90% RH (Non-Condensing)           Operating Temperature         32°~114°F (0~+45°C)           Power Supply         100 - 220VAC           Power Consumption         35W (with 2 HDD)           Dimension(WxHxD)         17.2 x 3.5 x 14in (435.7 x 88.7 x 356mm)           Net Weight         9.9lb (4.5kg) (without HDD)   |                           |  |  |
| Alarm 16 Input / 1 Output (Terminal Block)  Serial Port 1 RS485 (Terminal Block)  USB 2 USB2.0, 1 USB3.0  Rack Mountable Rack Ears Included  Operating Humidity 0~90% RH (Non-Condensing)  Operating Temperature 32°~114°F (0~+45°C)  Power Supply 100 - 220VAC  Power Consumption 35W (with 2 HDD)  Dimension(WxHxD) 17.2 x 3.5 x 14in (435.7 x 88.7 x 356mm)  Net Weight 9.9lb (4.5kg) (without HDD)   |                           |  |  |
| Serial Port         1 RS485 (Terminal Block)           USB         2 USB2.0, 1 USB3.0           Rack Mountable         Rack Ears Included           Operating Humidity         0~90% RH (Non-Condensing)           Operating Temperature         32°~114°F (0~+45°C)           Power Supply         100 - 220VAC           Power Consumption         35W (with 2 HDD)           Dimension(WxHxD)         17.2 x 3.5 x 14in (435.7 x 88.7 x 356mm)           Net Weight         9.9lb (4.5kg) (without HDD)   |                           |  |  |
| USB 2 USB2.0, 1 USB3.0  Rack Mountable Rack Ears Included  Operating Humidity 0~90% RH (Non-Condensing)  Operating Temperature 32°~114°F (0~+45°C)  Power Supply 100 - 220VAC  Power Consumption 35W (with 2 HDD)  Dimension(WxHxD) 17.2 x 3.5 x 14in (435.7 x 88.7 x 356mm)  Net Weight 9.9lb (4.5kg) (without HDD)   |                           |  |  |
| Rack Mountable Rack Ears Included  Operating Humidity 0~90% RH (Non-Condensing)  Operating Temperature 32°~114°F (0~+45°C)  Power Supply 100 - 220VAC  Power Consumption 35W (with 2 HDD)  Dimension(WxHxD) 17.2 x 3.5 x 14in (435.7 x 88.7 x 356mm)  Net Weight 9.9lb (4.5kg) (without HDD)   |                           |  |  |
| Operating Humidity         0~90% RH (Non-Condensing)           Operating Temperature         32°~114°F (0~+45°C)           Power Supply         100 - 220VAC           Power Consumption         35W (with 2 HDD)           Dimension(WxHxD)         17.2 x 3.5 x 14in (435.7 x 88.7 x 356mm)           Net Weight         9.9lb (4.5kg) (without HDD)   |                           | · · · · · · · · · · · · · · · · · · ·                  |  |
| Operating Temperature         32°~114°F (0~+45°C)           Power Supply         100 - 220VAC           Power Consumption         35W (with 2 HDD)           Dimension(WxHxD)         17.2 x 3.5 x 14in (435.7 x 88.7 x 356mm)           Net Weight         9.9lb (4.5kg) (without HDD)  |                           |  |  |
| Power Supply         100 - 220VAC           Power Consumption         35W (with 2 HDD)           Dimension(WxHxD)         17.2 x 3.5 x 14in (435.7 x 88.7 x 356mm)           Net Weight         9.9lb (4.5kg) (without HDD)  | 3                         | 3/   |  |
| Power Consumption         35W (with 2 HDD)           Dimension(WxHxD)         17.2 x 3.5 x 14in (435.7 x 88.7 x 356mm)           Net Weight         9.9lb (4.5kg) (without HDD)  |                           |  |  |
| Dimension(WxHxD)         17.2 x 3.5 x 14in (435.7 x 88.7 x 356mm)           Net Weight         9.9lb (4.5kg) (without HDD)   |                           |  |  |
| Net Weight 9.9lb (4.5kg) (without HDD)   |                           | · '  |  |
|  |                           |  |  |
| Conformity Certifications   FCC, CE, UL  |                           | \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \                  |  |
|  | Conformity Certifications | FCC, CE, UL  |  |